



Centrifugal · Oil-Free

H1500 Centrifugal Air Compressor

Large-scale centrifugal compressor for high-volume continuous air supply in heavy industrial environments.

TECHNICAL SPECIFICATIONS

Model	H1500
Type	Centrifugal (Oil-Free)
Flow Rate	141 – 195 m ³ /min
Discharge Pressure	2 – 12 bar-G
Motor Power	500 – 1,200 kW
Dimensions (L×W×H)	4500 × 2300 × 2800 mm
Unit Weight	11 – 14 T
Cooling Method	Water-cooled intercooler
Control System	PLC + LCD Touchscreen
Communication	Modbus Protocol
Lubrication	Oil-free
Bearing Type	5-pad tilting pad bearings
Standards	IEC / GB

KEY FEATURES

- ▶ **100% Oil-Free Output** — Advanced labyrinth sealing ensures zero oil contamination in the compressed air stream — suitable for sensitive process applications.
- ▶ **Anti-Surge Protection** — Real-time pressure monitoring with automatic surge-line compensation — reduces energy use and protects the machine.
- ▶ **Straight-Tube Intercooler** — Removable straight-tube heat exchangers for easy cleaning. Corrosion-resistant construction for long service life.
- ▶ **3D Swept Impeller** — Five-axis CNC machined backward-swept impeller blades for high aerodynamic efficiency and fatigue resistance.
- ▶ **PLC Intelligent Control** — LCD touchscreen with real-time parameter display, automatic alarm and interlock shutdown. Modbus integration ready.
- ▶ **AGMA Grade 13 Gearbox** — Forged alloy-steel gearbox with carburized tooth surfaces for high load capacity and long service life.

Hovol Air — a product line of Hovol Global

Qingdao Hongwo Trading Co., Ltd. (青岛宏渥商贸有限公司)

Rm 4, 6/F, Zhongxin Bldg, No. 247-263 Liaoning Rd, Shibei District, Qingdao, Shandong, China

Centrifugal specs measured at 35°C, 80% RH, 100 kPa inlet, 32°C cooling water. Subject to change; custom configurations available.

hovol-global.com

tomas@hovolglobal.com

WhatsApp / Tel: +86 188 0025

0771